



# HYDROCONNECT The electricity– producing fish lift

Double rotating hydropower screw with integrated fish lift for upstream and downstream migration of fish and microorganisms in flowing water



## (Why) HYDROCONNECT's hydropower screw

In light of the currently existing EU Water Framework Directive, operators of small hydroelectric power plants are struggling as much as large energy providers with its implementation.

"Nature and technology must not be a contradiction. The original principle of the Archimedean screw conveyor has found two applications in the **HYDROCONNECT** hydropower screw: energy generation with simultaneous injury-free transportation of fishes and micro-organisms."

The HYDROCONNECT combination system consisting of a hydropower screw AND a fish lift makes it possible for the first time to have easy and economical revitalisation as well as efficient new construction. With it, HYDROCONNECT has the solution for owners of water rights to fulfil the fish passage of power plants called for in the EU Water Framework Directive and at the same time, it makes electricity production possible.

The EU has stipulated improvements in Europe's waters since 2000. This includes the requirement to achieve fish passage in both directions of the respective flowing water by 2027 at the latest. The legal requirement to build fish ladders has existed for a long time. However, most existing ones cannot be described as bidirectional fish passage systems.

The electricity producing HYDROCONNECT hydropower screw with integrated fish lift now makes it possible for fishes to migrate upstream as well as downstream, and it does so completely without injury and in a resource-saving and energy-efficient way.

## Benefits for the environment and economy



Injury-free upstream and downstream migration of fish and other river life confirmed in various studies



Optimised guiding current makes it possible for fish to find their way into the fish ascent screw (EU patent)



Green system

Even microorganisms can pass through without harm

### Low space requirements

courses

Low amount of construction work and sleek construction even for gorges and small water-







**Energetic utilisation** of the residual water



High energy efficiency (65–70%) thanks to the gap-free drum design, even at low water



Amortisation possible from electricity production



Low noise therefore optimally suited for use in populated regions

## A variety of application areas

Due to its dual use as a fish lift and electricity generator, the hydropower screw is the most efficient solution at many locations and in many situations. Besides the EU required fish passage, the HYDRO-

CONNECT hydropower screw pays for itself due to the efficient electricity production depending on the location and flow rate.

- → Existing (run of river) power plants for fish ascent and descent incl. energy production
- → Small hydropower plants as independent power plants
- → Diversion power plants as a residual water machine
- → Supplement to turbines as a fish lift
- → Replacement for conventional fish ascent aids on existing dam stages and migration obstacles
- → Water pumping station for irrigation and/or storage power plants





		10000
Head:	3,7 m	100
Lenght:	14 m	
Weight:	17 t	5
River:	Alm	
Capacity:	1200l/s	2000
Pilot fish:	Trout (up to 90 cm)	
A LANGE TO THE		1210



eßnitz power p	lant, Neubruck, Lower Austria
Head:	3,32 m
Total diameter:	2 m
River:	Jeßnitz, Lower Austria
Pilot fish:	Brook trout (30 cm), bullhead (accompanying fish s
Biggest possible fish:	90 cm

The HYDROCONNECT hydropower screw has an empty weight of 14.5 tons and maximum water flow rate of 1000 l/sec. On the JeBnitz, the substrate-bound bullhead profits in particular from the connection to the bottom, which makes effortless fish migration possible.

### Fish discharge chute

- chute to transport the individually ascended fish into the calm headwater
- minimum slope
- can be disassembled

### Generator works

- Generator
- GearboxBrake

By varying the operating speed, the supply can be adjusted to the water flow. This variation possibility is realised through the implemented frequency converter technology.

With a planned shutdown, the hydropower screw can be actively driven in order to empty it (protection against icing).

Spring-loaded brakes are used for braking, which are triggered by electromagnets. The brake is applied automatically in the event of a power outage.

### Intake gate

steel protection for blocking the inlet or alternatively to regulate the water quantity
self-closing in the event of a power outage

### Steel construction

- welded steel construction
- screw blades welded throughout
- high stability
- long service life
- gap-free
- large-scale corrosion protection

## Electricity + fish migration: How it works

The HYDROCONNECT hydropower screw with double rotating cylinders is based on the Archimedean principle, the operating principle of a hydropower screw. There is an outer sheath with a headrace screw that contains an inner, counter-rotating, spiral fish transport screw, which pumps water into the headwater. Power generation is made possible by a drum (rotating cylinder) with a casing pipe that is seamlessly welded to the screw blades. The system is mounted on the outer shell by roller bearings, through which high heads are possible.

The flow of water from the exiting headrace and the central luring current are used to guide fish wanting to reach the upper level to the inner fish lift. As soon as they swim into the entrance, which reaches down as far as the river bed, they are transported gently upwards in the screw chamber in the constantly filling water. Afterwards, the fish end up in the headwater via a fish discharge chute. The water transported to this upper level is ready once again for reuse by the plant or alternatively for the fish to make their way down.

### Seals

- rubber seal in the headwater (underwater) area
- long service life
- easy to replace
- adjustable

### Substructure

possible as a concrete structure or steel frame

### Control system

- speed and displacement controllable by means of a level sensor or manual input
- can be configured as an independent system

## Hydraulic lifting frame makes it possible to offload the

rotating cylinder during maintenance and to replace the rollers.

### Cover/housing

Built to be waterproof on request including design variations (wood, glass, stone, concrete, etc.)

#### **Roller** bearing

As part of the main bearing the radial forces get absorbed by heavy-duty rollers • no underwater storage required

• big fall heights possible

### Walk-on

### maintenance gangway

for maintenance and cleaning of the system

### Fish ascent & descent (patented double screw)

The fish transport is based on Archimedes' principle: Fish are raised effortlessly upstream or alternatively downstream in the standing water of the inner or alternatively outer screw chamber.

- special shape of the screw blades to create an optimised guiding current
- bottom connection for fish that are weak swimmers such as the bullhead, for example



You can find function videos at www.hydroconnect.at/en/videos

## Future solution, fish descent

"Fish need a humane solution to overcome unnatural obstacles."

Through the generation of a real luring or guiding current, HYDRO-CONNECT makes it possible for the fish to enter in the intended direction. This is ensured through a patented technology: the double screw as well as the roller bearing. By connecting to the bed, ascent is also made possible to fishes that are weak swimmers or substrate-bound such as the bullhead, for example.

That way it is possible for fish and microorganisms to pass transverse structures upstream and downstream safely, effortlessly and quickly, which is a requirement of the EU Water Framework Directive that operators of small power plants and hydropower plants have to meet by 2027 at the latest.

From this fish ecology approach, the topic of fish ascent was researched together with the Institute for Hydrobiology and Water Management (IHG) of the University of Natural Resources in Vienna (BOKU).



View of fish descent in the outer pipe, still picture of the fish ecology accompanying research at the Jeßnitz river in Lower Austria, 2014





## Safe fish transport proven

Fish ecology studies in the form of accompanying research on the HYDROCONNECT hydropower screw with integrated fish lift were carried out by BOKU, the University of Natural Resources in Vienna, Institute for Hydrobiology and Water Management from 2012 - 2014. Starting with the first trials between December 2011 and March 2012, juvenile and adult trout and bullheads ascended without injury.

In studies conducted in March 2012, 151 of 372 individuals of the main fish species, i.e. brook trout. rainbow trout, bullhead and grayling (fish lengths between 3 and 48 cm = juvenile and adult individuals of all four species) ascended via the inner pipe screw.

In another ascent trial in December 2013 with the expanded fish species aitel, barbel, sneep, roach, pike and Danube salmon, 75% of the fish ascended.

In the descent study in March 2014 with 140 fish (bullhead, brook and rainbow trout), at total of 56% descended (Fig. 1) and numerous individuals ascended again (total use Fig. 2). This secures an ecological balance and the fish population.

### Conclusion of the Institute for Hydrobiology and Water Management (IHG/BOKU):

- → <u>No injuries</u> for fish ascent and descent with the HYDROCONNECT hydropower screw
- → Functionality of the fish ascent screw confirmed for the fish ecology coenosis model of the River Jeßnitz.
- → The hydropower screw from Hydroconnect is very well suited for fish descent

Data origin: Fish ecology studies of the "HYDROCONNECT" hydropower screw with the "Albrecht fishLift inside" at the Jeßnitz power plant location; Bernhard Zeiringer, Maxim Grigull and Stefan Auer



Fig. 1 Ascent and descent of domestic fish of various sizes and stages of life, March 2014



Fig. 2: Total use of the bidirectional transport (ascent and descent) of bullhead, rainbow trout and brook trout, March 2014.



## Frequent questions & answers

### How high is the efficiency of the HYDROCONNECT hydropower screw?

The mechanical efficiency is up to 90%. This results in electrical efficiency, minus all the mechanical losses, of 65% even for small systems - even at low water. In larger systems, the electrical efficiency increases to 70% and more.

### Is the HYDROCONNECT hydropower screw with integrated fish lift suitable for all fishes, or more precisely will the fishes in my waters fit through the screw tube?

The screw diameter is oriented in any case around the predominant fish in the waters in order to comply with the EU Water Framework Directive. Each location is planned separately, and the machine size is defined according to financial and ecological criteria. Drum diameters of up to four metres are possible. Hence, this system provides up to 170 cm of space (in both directions) for the predominant fish species.

### For what designated uses and heads is the HYDROCONNECT hydropower screw suitable?

Installation sites and possible uses of the Hydroconnect hydropower screw with integrated fish lift are:

- $\rightarrow$  existing reservoirs and migration obstacles
- $\rightarrow$  existing (run of river) power plants for fish ascent and descent incl. energy production
- → small hydropower plants as independent power plants
- → diversion power plants as a residual water machine
- $\rightarrow$  water pumping station for irrigation and/or storage power plants

In the process, the hydropower screw handles water volumes of 0.2 m3/s to 5.0 m3/s and heads of 2 to a maximum of 20 m (possibly also higher). The roller bearing makes it practically independent of the supply and head.

### What benefits are offered by the HYDROCONNECT hydropower screw with double rotating cylinders?

Besides efficient, fish-friendly electricity production, the hydropower screw with double rotating cylinders makes it possible for fish to ascend and descend. Through the compact design with an integrated fish lift, an economical and self-amortising installation can also be realised at existing power plants and other transverse structures.

### *Is the HYDROCONNECT system only for the* passage of specific fish species?

No, the hydropower screw with double rotating cylinders with integrated fish lift is for the passage of the strongest and weakest swimming species of fish at all stages of life. You can find out more on this on page 9 of this brochure.

### What is the advantage of a roller bearing over conventional underwater mounting?

Thanks to the roller bearing, high heads in steep terrain are possible without any risk of the screw sagging. In contrast to underwater mounting, the roller bearing makes it possible for fish to enter the fish ascent without obstruction and without injury.

### Are fish wary of the transport?

No. Many years of studies as well as numerous underwater videos show the calm, almost playful way of using the fish lift. Also, the results of the ascent and descent studies and in particular the multiple use of the lift prove that fish are neither wary nor afraid of it. This is due to the fish-friendly transport of the energy-saving technology (the fish ascends in the calm water of the auger flight) and the extremely short transport path for the fish.

### Are the fish sucked into the hydropower screw?

No. The lower screw area is designed and patented so that it creates an optimised guide current for fish and water life. That way the fish find the way via the fish ladder without being forced to do so. There is a current leading to the screw in the bottom area of the entry, which is very well suited for fish and microorganisms that are weak swimmers.

## Data & Facts on **HYDROCONNECT**

accompany

optor Maltor Albr

2011	Ī	first prototype is create
Ecological npanying research	•	Ongoing trials and more in Vienna (BOKU) show nisms with the HYDRC
2013	•	Hydro-Connect GmbH
2014	•	At the "Forum of the Fi 2014, experts gave top power screw.
VERBUND AG as first customer	•	HYDROCONNECT rec ruct a fish lift at the Re spring 2015
Numerous awards	•	3rd place in the Green mental prize, 3rd place <b>the Austrian State Pr</b>
Official confirmation	•	Due to many positive p and electricity-producin screw), the Federal Mir approval and the <b>state</b> was included in the <b>co</b>

### Can logs, branches and various floating debris become trapped in the screw?

No. Trapping of branches or floating debris is extremely unlikely, because there are no constrictions or bottlenecks in the screw. A coarse screen in front of the intake grate keeps logs and large floating debris away.

cht develops an electricity-producing fish lift. The be

nitoring by the University of Natural Resources v the injury-free passage of fish and microorga-CONNECT hydropower screw.

l is founded.

ish Migration and Hydropower Initiative" in April o marks to the fish friendly and efficient hydro-

eives an order from VERBUND AG to consttznei power plant, which went into operation in

Business Award, winner of the special environe in NEPTUN Water Prize as well as winner of ize for the Environment and Climate 2015.

projects with HYDRO-CONNECT's fish pass ng fish pass (double rotating hydropower nistry confirmed its ability to obtain official e of the art. The HYDRO-CONNECT fish pass nstruction guidlines of fish pass 2021.



### HYDROCONNECT

Hydro-Connect GmbH Am Gries 5 3341 Ybbsitz Austria +43 (0) 720 720 900-800 office@hydroconnect.at www.hydroconnect.at

**Exclusive Partner** 





Publisher: Hydro-Connect GmbH, Am Gries 5, A-3341 Ybbsitz; Editing & Design: P&R Kommunikationsberatung und Mediengestaltung OG in cooperation with Hydro-Connect; Photos: Page 1, 4: Photo Markus Guggi, Page 2: Photo Weinfranz, 3D & graphics on pages 3, 6, 7, 9: P&R Kommunikationsberatung und Mediengestaltung OG, Photo page 5: Hans Peter Schlager, Page 8: Hydro-Connect; Print: druck.at, printed on wood-free, elementary chlorine-free paper in Austria